



ORDERING CODE	TYPE OF CURRENT	VOLTAGE (V)	POWER (W)	RESISTANCE (Ω) 68-77°F	CURRENT (A) COLD COIL - HOT COIL
EB1101220100	DC	12	20	7.5±7%	1.66 - 1.06
EB1102420100	DC	24	20	20.0±7%	0.88 - 0.53
EB1102620100	DC	26	20	34.2±7%	0.77 - 0.52
EB1102820100	DC	28	20	39.2±7%	0.71 - 0.50
EB1103620100	DC	36	20	64.0±7%	0.56 - 0.36
EB1202420100	RAC	24	20	23.2±7%	0.95 - 0.63
EB1211020100	RAC	110	20	470.0±7%	0.19 - 0.14
EB1222020100	RAC	220	20	1910.0±7%	0.09 - 0.07

TYPE OF CONNECTOR	DIN43650-ISO4400
HEAT INSULATION CLASS	H (180°C / 356° F)
AMBIENT TEMPERATURE RANGE	-30 ÷ 60°C / -86 ÷ 140°F
WEIGHT	0.22 kg
ENCAPSULATING MATERIAL	PET

Inlet voltage fluctuation must not exceed ±10% of nominal voltage to guarantee correct operation and long life of coil

Available different voltages