



| ORDERING CODE | TYPE OF CURRENT | VOLTAGE (V) | POWER (W) | RESISTANCE (Ω) 68-77°F | CURRENT (A) COLD COIL - HOT COIL |
|---------------|-----------------|-------------|-----------|------------------------------------|-------------------------------------|
| EB1101020200 | DC | 10 | 20 | 5.0±8% | 1.98 - 1.28 |
| EB1101220200 | DC | 12 | 20 | 7.5±7% | 1.66 - 1.06 |
| EB1102020200 | DC | 20 | 20 | 7.5±7% | 0.99 - 0.65 |
| EB1102420200 | DC | 24 | 20 | 20.0±7% | 0.88 - 0.53 |
| EB1102620200 | DC | 26 | 20 | 34.2±7% | 0.77 - 0.52 |
| EB1102820200 | DC | 28 | 20 | 39.2±7% | 0.71 - 0.50 |
| EB1103620200 | DC | 36 | 20 | 64.0±7% | 0.56 - 0.36 |
| EB1104820200 | DC | 48 | 20 | 110.0±7% | 0.45 - 0.28 |

| | |
|---------------------------|--------------------------|
| TYPE OF CONNECTOR | AMP JUNIOR |
| HEAT INSULATION CLASS | H (180°C / 356° F) |
| AMBIENT TEMPERATURE RANGE | -30 ÷ 60°C / -86 ÷ 140°F |
| WEIGHT | 0.22 kg |
| ENCAPSULATING MATERIAL | PET |

Inlet voltage fluctuation must not exceed ±10% of nominal voltage to guarantee correct operation and long life of coil

Available different voltages